

SLICK ALL PURPOSE DRY LUBRICANT & RELEASE AGENT

DANGER: Extremely flammable aerosol. Contains gas under pressure; may explode if heated. May be fatal if swallowed and enters airways. Causes skin and serious eye irritation. May cause drowsiness or dizziness. Keep away from heat, sparks, open flames, and hot surfaces. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Wash hands thoroughly after handling. Wear protective gloves and eye protection. Specific treatment (see FIRST AID section on this label). Avoid breathing spray. Use only outdoors or in a well-ventilated area. Protect from sunlight. Do not expose to temperatures exceeding 122°F. Store locked up in a well-ventilated place. Dispose of container to recyclables when completely emptied. Use with adequate ventilation. Intentional misuse by concentrating and inhaling the product can be harmful or fatal. **KEEP OUT OF REACH OF CHILDREN.**

FIRST AID: IF SWALLOWED: Immediately call a POISON CONTROL CENTER. Do NOT induce vomiting. **IF INHALED:** Remove person to fresh air and keep comfortable or breathing. Call a doctor if you feel unwell. **IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice. **IF ON SKIN:** Wash off with soap and water. If skin irritation occurs: Get medical advice. Take off contaminated clothing and wash it before reuse.

CONTAINS (CAS No.): heptane (142-82-5); acetone (67-64-1); and liquefied petroleum gases.



Sold By:
SUNBELT LABORATORIES
P.O. BOX 1563
STAFFORD, TX 77497-1563
281-261-4747/1-800-324-4413

See Safety Data Sheet for complete safety information.
24 HOUR MEDICAL EMERGENCY: 1-866-836-8855
Made in the USA with globally sourced materials.



www.sunbelt-labs.com

P.O. BOX 1563 • STAFFORD, TX 77497 • 281-261-4747/1-800-324-4413

SLICK ALL PURPOSE DRY LUBRICANT & RELEASE AGENT

USE ON ANY SURFACE: METAL, GLASS, RUBBER, PLASTIC, PAINTED FINISHES AND FABRICS

STOPS STICKING - Drawers, windows, doors, screens, zippers, locks, etc.

ELIMINATES - annoying squeaks in hinges, latches, springs, etc.
RETARDS CORROSION - protects battery terminals, tools, guns, skates, aluminum windows and doors.

HELPS PREVENT - grass, dirt and mud from sticking to lawn mowers - snow from sticking to snow shovels.

DRIES FAST - leaves no greasy or oily film - not affected by water, oil or solvents.

HEAT STABLE - will not freeze or melt.

USES

PLASTIC MOLDING - Release agent for injection and compression moldings.

PACKAGING - Prevents waxes, adhesives and plastics from sticking to heat sealer bars. Reduces clean-up time. Eliminates friction on guide rails, line conveyors, scramble tables, etc.

CONVERTORS AND PRINTERS - Eliminates glue build-up on working surfaces. Reduces friction on paper cutters, knives, drills, etc.

INDUSTRIAL - For industrial blenders, bins, conveyors, paper, leather, textile and paper mill dry cans, plating screens, glass, fiber, fabric, hosiery forms, container coating for easy release of sticky contents.

AUTOMOTIVE - Lubricates window channels, door, weather stripping, trunk seals, undercarriage, rubber mounting, emergency brakes, pedal shafts, car seats, adjustment mechanisms. Eliminates squeaks from fan belts (apply when running). Prevents battery terminal corrosion. Waterproofs ignition system, hinges, springs and casters.

GARMENT - Promotes slip on sewing machine beds, cutting tables and dies. Prevents bunching of fabrics during sewing operation.

DIRECTIONS

Thoroughly clean the surface to be sprayed. Spray a light film with a sweep motion. When used on sticking surfaces work object back and forth. Spray again if necessary.



PLEASE RECYCLE
WHEN EMPTY

SUNBELT

Slick

All Purpose Dry Lubricant & Release Agent

- ★ **STOPS STICKING**
- ★ **HEAT STABLE**
- ★ **RETARDS CORROSION**
- ★ **FAST DRYING**

DANGER: EXTREMELY FLAMMABLE AEROSOL.
CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED.
MAY BE FATAL IF SWALLOWED AND ENTERS AIRWAYS.
Read carefully other cautions on back panel

NET WT : 12 oz. (340 g)